

667109010 ECO THERMAL FRUIT TAG (BPA FREE) 210 TC

Face A white non-topcoated thermal paper laminated with cavitated PP, tear resistant, designed for fruit bag tags.



ECO TH. FRUIT TAG (BPA F.) 210 TC	

Face	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	145 ± %5
Thickness	ISO 534	µm	210 ± %5

Slit Rolls

Width	ISO 534	mm	± 1
Roll length measurement	ISO 534	m	± %1

Application and Use

This laminate generally is used as tags in the food industry. The product can be used onto a net of fruit or other food products.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Conversion and Printing

This product has good printability in all classical printing methods. Printing inks should be checked for suitability prior to use. This product is designed for use in thermal printing system at printing speeds up to 8 inch /200 mm per sec (based on printer's set up).

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22°C ± 2°C with a relative humidity of 50 %, ± 5%.

Disclaimer: The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. All specific substrate specifications may vary by ±10%. They are intended to inform and advise and are subject to influence from the technical process. This edition with the indicated date below replaces all previous editions. With the present edition all older editions are null and void.