


653037001 ECO THERMAL FSC (BPA FREE)-P100-YG

Face A white, non-topcoated FSC mix credit thermal paper that is coated with black imaging thermosensitive coating. This paper has limited resistance to thermal image scratching or smudging with normal stability against oil, alcohol and environmental influences such as heat, humidity and light. The image may fade over a period of time if exposed to high humidity and light. This paper is BPA-free.

Adhesive An acrylic-based, strong permanent adhesive designed for general-purpose applications. It provides excellent initial tack and adhesion across a wide variety of substrates. It ensures superior performance during slitting, high-speed matrix stripping and automatic labeling processes.

Liner Yellow, supercalendered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.



ECO THERMAL FSC (BPA FREE)	
P100	
YG	

Face	Method	Unit	Target
------	--------	------	--------

Basis Weight	ISO 536	g/m ²	70
--------------	---------	------------------	----

Thickness	ISO 534	µm	74
-----------	---------	----	----

Adhesive

Peel adhesion 90°	FTM 2 st. st	N/m	240	(6 N/25mm)
-------------------	--------------	-----	-----	-------------

Loop Tack	FTM 9 glass	N/m	480	(12 N/25mm)
-----------	-------------	-----	-----	-------------

Min. appl. Temperature		°C	0
------------------------	--	----	---

Service Temperature		°C	-20 / +80
---------------------	--	----	-----------

Liner

Basis Weight	ISO 536	g/m ²	53
--------------	---------	------------------	----

Thickness	ISO 534	µm	46
-----------	---------	----	----

Transparency	DIN 53147	%	49
--------------	-----------	---	----

Laminate

Thickness	ISO 534	µm	130 ± %10
-----------	---------	----	-----------

Slit Rolls

Width	ISO 534	mm	± 1
-------	---------	----	-----

Roll length measurement	ISO 534	m	± %1
-------------------------	---------	---	------

Application and Use

Typical applications are information labelling such as logistics and warehousing, stores mainly on paper, cardboard, plastic bags. Limited resistance to moisture, oil , fats and plasticizers and short term durability recommended for strong lighting to avoid image fade.

Conversion and Printing

This product has good printability in all classical printing methods. Printing inks should be checked for suitability prior to use. This product is designed for use in thermal printing system at printing speeds up to 10 inch /250 mm per sec (based on printer's set up).

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

One year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.