

**652901550 THALES CREME WS FSC-WL770-WG 80**

|                 |                                                                                                                                                                                        |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Face</b>     | Creme, Wet-strength, FSC mix credit woodfree thales textured printing paper, specially designed for premium Wine & Spirits labeling applications.                                      |
| <b>Adhesive</b> | A permanent, acrylic based, water resistant adhesive especially designed for wine&spirits industry.                                                                                    |
| <b>Liner</b>    | White, supercalendered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system. |



|                     |  |
|---------------------|--|
| THALES CREME WS FSC |  |
| WL770               |  |
| WG 80               |  |

| Face                    | Method       | Unit             | Target    |              |
|-------------------------|--------------|------------------|-----------|--------------|
| Basis Weight            | ISO 536      | g/m <sup>2</sup> | 90        |              |
| Thickness               | ISO 534      | µm               | 140       |              |
| <b>Adhesive</b>         |              |                  |           |              |
| Peel adhesion 90°       | FTM 2 st. st | N/m              | 260       | (6,5 N/25mm) |
| Loop Tack               | FTM 9 glass  | N/m              | 560       | (14 N/25mm)  |
| Min. appl. Temperature  |              | °C               | +5        |              |
| Service Temperature     |              | °C               | -20 / +80 |              |
| <b>Liner</b>            |              |                  |           |              |
| Basis Weight            | ISO 536      | g/m <sup>2</sup> | 80        |              |
| Thickness               | ISO 534      | µm               | 65        |              |
| Transparency            | DIN 53147    | %                | 40        |              |
| <b>Laminate</b>         |              |                  |           |              |
| Thickness               | ISO 534      | µm               | 217 ± %10 |              |
| <b>Slit Rolls</b>       |              |                  |           |              |
| Width                   | ISO 534      | mm               | ± 1       |              |
| Roll length measurement | ISO 534      | m                | ± %1      |              |

**Application and Use**

This product is designed for wine&spirits application. For best performance, bottles should be dry and clean prior to application. Product can be used with limited ice bucket performance.

**Conversion and Printing**

Surface is suitable for excellent printing quality by all conventional print technologies and sheet, fed offset, flexographic printing.

**Packaging**

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

**Shelf Life and Storage Conditions**

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Disclaimer: The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. All specific substrate specifications may vary by ±10%. They are intended to inform and advise and are subject to influence from the technical process. This edition with the indicated date below replaces all previous editions. With the present edition all older editions are null and void.