





We have perfected this aspect by developing advanced adhesive solutions specifically designed for wet wipes labels. Our adhesives are engineered to maintain their strength and durability, even in challenging conditions like exposure to moisture and frequent handling. By combining innovative adhesive formulations with high-quality materials, we ensure that the labels reliably seal each time, supporting both product longevity and consumer satisfaction.



	PP CLEAR 90 TC-RS730-W	G_D	PP CLEAR 50 TC-RS730-WG_D
Face Basis Weight Thickness	80 ± 5 90 ± 3		45 ± 3 50 ± 3
Adhesive Peel Adhesion 90° Loop Tack Min. Appl Temperature Service Temperature		min. min. (20 /	200
Liner Basis Weight Thickness	58±2 50±3		58±2 50±3
Laminate Thickness	160±%10		108±%10
Width Slit Rolls		±	1



	PP SOLID WHITE 60 TC-RS730-WG 70_D		PP CLEAR 60 NTC -RS730- WG_D
Face Basis Weight Thickness	48 ± 3 50 ± 3		54 ± 2 58 ± 3
Adhesive Peel Adhesion 90° Loop Tack Min. Appl Temperature Service Temperature		min. min. C -20 /	200
Liner Basis Weight Thickness	58±3 50±4		58±3 50±4
Laminate Thickness	160±%10		120±%10
Width Slit Rolls	±1		



	PP SOLID WHITE 50 NTC-RS730-WG 70_D	PP SOLID WHITE 90 TC -RS730- WG_D
Face Basis Weight Thickness	48 ± 3 50 ± 3	80±5 90±5
Adhesive Peel Adhesion 90° Loop Tack Min. Appl Temperature Service Temperature	min	. 100 . 200 0 / +80
Liner Basis Weight Thickness	70±2 60±3	58±3 50±4
Laminate Thickness	128±%10	160±%10
Width Slit Rolls	±1	



PET CLEAR 75 -RS730- WG_D				
Face Basis Weight Thickness	105 ± 2 75 ± 3			
Adhesive Peel Adhesion 90° Loop Tack Min. Appl Temperature Service Temperature	min. 100 min. 200 0 -20 / +80			
Liner Basis Weight Thickness	58±2 50±3			
Laminate Thickness	138±%10			
Width Slit Rolls	±1			