



# Frimpeks Waterbased Varnishes

102223 WATER BASED COATINGS GLOSS 51203

### **Product Information:**

102223 is a gloss protective overprint lacquer. Suitable for separate and in line coating units and both for wet-on-wet and wet-on-dry applications. It is used in lacquering of cardboards and coated papers to get slip, gloss and protective property. It is also suitable for packaging of detergent, soap.

# **Typical End Use**

Magazines, Posters, Brochures, Leaflets, Packaging

## **Typical Properties**

Fast curing, Excellent rub and scratch resistance, High resistance to light (non yellowing), can be processed immediately

# At a Glance

Gluable/Imprintable No Flexibility Very Good Mechanical Resistance Good Suitable for In-Line Yes Can be Applied via Pump Yes Suitable Direct Food Contact No

#### **Technical Data**

8.0 - 8.5Solid Content (130°C /3h) 35 - 38 %

Viscosity @ 22°C Ford Cup  $35 - 45 \sec$ Odor Low Gloss

75+ at 60° Reflection

# **Recommended Application**

This product is designed to be applied through the varnishing unit of an offset press.

To get the optimal performance the recommended application is app 3-4 Gr/m

# **Processing**

Please make your own tests, for the needed specific demands, before extended production periods.

#### **Equipment and Drying**

Depends on the efficiency of the dryer, the quantity of coating applied and the substrate

# Cleaning

Appliance and other equipment can be cleaned with water after use.

# **Shelf Life and Storage Conditions**

Water based varnish cans and drums must be store tightly closed where in door conditions are protected from continuous sun light and temperatures higher than 40°C

White

NORMAL STRORAGE DURATION: 1 year

#### Safety

Liquid Appearance

During handling and use the user should avoid inhalation of vapors as well as direct eye or skin contact. Protective eyewear and latex gloves are recommended while using this product. Consult the SDS for additional handling and safety information.

### **Packaging**

This product is available in: 200 KG Iron Drums 1000KG IBC

#### **Transportation**

Non-dangerous goods. Cannot be transported in freezing temperatures, and product should be brought to room temperature prior to use.

The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. They are intended to inform and advise and are subject to influence from the technical process.

This edition of August 5, 2021 replaces all previous editions. With the present edition all older editions are null and void.

#### Frimpeks Kimva ve Etiket Sanavi Ticaret A.S.