

654151500
PP MATT WHITE 65 TC-R410-WG

Face	A white matt, polypropylene film with high opacity, whiteness, and good printability.
Adhesive	Acrylic based, removable adhesive for general use with long term removability.
Liner	White, supercalandered siliconised glassine paper. Specially designed for high-speed conversion, punching and perforation. Transparency allows its use in automatic dispensing

Face	Method	Unit	Target	
Basis Weight	ISO 536	g/m ²	47 ± 3	
Thickness	ISO 534	µm	65 ± 5	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min.80	(min. 2 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.180	(min. 4.5 N/25mm)
Min. appl. temperature		°C	+5	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 536	g/m ²	56 ± 2	
Thickness	ISO 534	µm	49 ± 3	
Transparency	DIN 53147	%	51	
Laminate				
Thickness	ISO 534	µm	125 ± 5	

Application and use

For use in labelling of the products where completely clean surface is required after peeling the label.

Conversion and Printing

Topcoated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing.

Packaging

The rolls are slit according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.