

672601415
INKJET GLOSS -PE300- WG_D

Face	Special coated gloss finished paper. It is suitable for high resolution, multicolor inkjet printing.
Adhesive	Acrylic based, strong permanent adhesive for general use. This adhesive gives excellent initial tack and adhesion even on a wide variety substrates including apolar, rough and curved substrates. Edge bleeding may occur.
Liner	White, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

Face	Method	Unit	Target	
Basis Weight	ISO 536	g/m ²	86 ± 4	
Thickness	ISO 534	µm	102 ± 6	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min.275	(min. 6,875 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.550	(min. 13,75 N/25mm)
Min. appl temperature		°C	+5	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 536	g/m ²	58 ± 3	
Thickness	ISO 534	µm	50 ± 3	
Transparency		%,75°	51	
Laminate				
Thickness	ISO 534	µm	165 ± 5	

Application and use

This product is designed for high resolution, multicolor inkjet printing.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Conversion and Printing

Surface is specially designed for inkjet printing. The print results need to be checked when other printing technologies are used.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.