

**672651280**
**INKJET MATT -PE300- WG\_D**
**672651280**

<b>Face</b>	Special coated matt finished paper. It is suitable for high resolution, multicolor inkjet printing.
<b>Adhesive</b>	Acrylic based, strong permanent adhesive for general use. This adhesive gives excellent initial tack and adhesion even on a wide variety substrates including apolar, rough and curved substrates. Edge bleeding may occur.
<b>Liner</b>	White, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>	
Basis Weight	ISO 536	g/m <sup>2</sup>	85 ± 4	
Thickness	ISO 534	µm	106 ± 6	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min.275	(min. 6,875 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.550	(min. 13,75 N/25mm)
Min. appl temperature		°C	+5	
Service temperature		°C	-20 / +80	
<b>Liner</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	60 ± 2	
Thickness	ISO 534	µm	51 ± 3	
Transparency		%,75°	51	
<b>Laminate</b>				
Thickness	ISO 534	µm	170 ± 5	

**Application and use**

This product is designed for high resolution, multicolor inkjet printing.

**Conversion and Printing**

Surface is specially designed for inkjet printing. The print results need to be checked when other printing technologies are used.

**Packaging**

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

**Shelf Life and Storage Conditions**

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.