

**651003000**
**COPYLASER -H400- W.KRAFT 55\_D**
**651003000**

<b>Face</b>	Matt, white, woodfree machine finished paper with good opacity. This paper is suitable for multifunctional information labelling, especially designed for ink jet, lasers and photocopiers.
<b>Adhesive</b>	Rubber based hotmelt, permanent adhesive for general use. Excellent adhesive performance on a wide variety of substrates including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures, we recommend to check suitability prior to use. Excellent performance during slitting, high speed matrix-stripping and automatic labelling.
<b>Liner</b>	White, woodfree kraft backing paper for optimal layflat performance. Specially designed for laminate where thin backing is needed.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>	
Basis Weight	ISO 536	g/m <sup>2</sup>	70 ± 3	
Thickness	ISO 534	µm	90 ± 3	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min.240 or PT	(min. 6 N/25mm or Paper Tear)
Loop Tack	FTM 9 glass	N/m	Min.480	(min. 12 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-30 / +70	
<b>Liner</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	53 ± 2	
Thickness	ISO 534	µm	55 ± 3	
<b>Laminate</b>				
Thickness	ISO 534	µm	152 ± 5	

### Application and use

This product is designed for the manufacture of A4 sheets for use in multifunctional information labelling at laser printers, copiers and inkjet printers. It is ideal for office use and information labelling such as address, instruction. The product has tight release property to avoid predispending during printing or copying process.

### Conversion and Printing

The material can be converted by the conventional roll-to-sheet conversion technologies.

### Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

### Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

### Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermerciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr  
 8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr  
 34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944