

651001260
DATA 70 -P100- W.SCK_D
651001260

Face	A matt white, woodfree machine finished paper with good opacity, high runnability, excellent absorption and toner bonding performance.
Adhesive	Acrylic based, permanent adhesive for general use. Suitable for numerous applications on clean, dry and flat surfaces, including slightly rough and curved substrates. It's not suitable for wet applications. Excellent performance during slitting, high speed matrix-stripping and automatic labelling.
Liner	SCK is a white, super calendared siliconised kraft paper with high internal strength, toughness, and tear resistance. Suitable for roll to roll label applications.

Face	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	70 ± 3
Thickness	ISO 534	µm	90 ± 3
Adhesive			
Peel adhesion 90°	FTM 2 st.st	N/m	min.380 or PT (min. 9,5 N/25mm or Paper Tear)
Loop Tack	FTM 9 glass	N/m	min.550 (min. 13,75 N/25mm)
Min. appl temperature		°C	0
Service temperature		°C	-20 / +80
Liner			
Basis Weight	ISO 536	g/m ²	65 ± 2
Thickness	ISO 534	µm	57 ± 3
Transparency		%,75°	53
Laminate			
Thickness	ISO 534	µm	155 ± 5

Application and use

For use in meto labelling, coupons and all printing jobs which a self-adhesive woodfree offset face is required.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Conversion and Printing

Suitable for ofset, flexography, letterpress printing methods and inkjet applications.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermerciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr
 8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr
 34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944