

595350130**MATT PET OPAQUE 130****595350130**

Matt surface A white matt, medium gloss polypropylene film with high opacity, whiteness and good printability.

Also surface A clear polyester liner giving optimum smoothness to the adhesive layer. High strength and uniform quality permit very high speed conversion and dispensing.

Face	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	160 ± 3
Thickness	ISO 534	µm	130 ± 3

Conversion and Printing

Matt surface, can be printed by a wide range of printing methods : Flexo, offset, uv rotary letterpress, silkscreen, etc .

Also surface is well suitable for thermal transfer printing.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermeciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr
8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr
34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944