

421008000**ONE SIDE COATED PAPER 80 G****421008000**

One side coated paper is designed for high-end, pressure sensitive label applications. This grade features excellent opacity and high brightness combined with a semi-gloss finish for excellent printability.

Face	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	78 ± 4
Thickness	ISO 534	µm	67 ± 4
CIE Whiteness		%	120.0
Opacity	ISO 2471	%	87.0
Gloss Hunter	ISO 8254-1	%	68.0
Roughness PPS10 TS		µm	1.0
Tensile Strength MD		kN/m	5.0
Tensile Strength CD		kN/m	2.2

Application and use

This product is designed for wide range of promotional and industrial labelling applications where a good semi gloss appearance is required.

Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermerciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr
8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr
34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944