

655002200
PE OPAQUE 85 NTC -R410- WG_D
655002200

Face	A white, opaque, corona treated polyethylene film that has very good die cutting performance.
Adhesive	Acrylic based, removable adhesive for general use with long term removability.
Liner	White, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

Face	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	80 ± 5
Thickness	ISO 534	µm	80 ± 5
Adhesive			
Peel adhesion 90°	FTM 2 st.st	N/m	min. 80 CP (min. 2 N/25mm)
Loop Tack	FTM 9 glass	N/m	min. 180 CP (min. 4,5 N/25mm)
Min. appl temperature		°C	+5
Service temperature		°C	-20 / +80
Liner			
Basis Weight	ISO 536	g/m ²	60 ± 2
Thickness	ISO 534	µm	53 ± 3
Transparency	DIN 53147	%	51
Laminate			
Thickness	ISO 534	µm	138 ± 5

Application and use

For use in labelling of the products where completely clean surface is required after peeling the label.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Conversion and Printing

Corona treated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing. In-line corona treatment, careful selection of the ink and trial ink performance before

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermereçiler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr
 8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr
 34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944