

**653102830**
**TOP THERMAL -DF710- W.SCK\_D**
**653102830**

<b>Face</b>	A white topcoated paper that is coated with black imaging thermosensitive coating. This paper has very good resistance to moisture, oil, fat, alcohol and plasticizers.
<b>Adhesive</b>	Acrylic based, permanent adhesive suitable for deep freeze applications onto cold and moist surfaces with very good adhesion at low temperature. Not suitable for labelling curved surfaces.
<b>Liner</b>	SCK is a white, super calendered siliconised kraft paper with high internal strength, toughness, and tear resistance. Suitable for roll to roll label applications.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>	
Basis Weight	ISO 536	g/m <sup>2</sup>	78 ± 5	
Thickness	ISO 534	µm	82 ± 5	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min.280 or PT	(min. 7 N/25mm or Paper Tear)
Loop Tack	FTM 9 glass	N/m	min.400	(min. 10 N/25mm)
Min. appl temperature		°C	-20	
Service temperature		°C	-40 / +70	
<b>Liner</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	65 ± 2	
Thickness	ISO 534	µm	57 ± 3	
Transparency	DIN 53147	%	53	
<b>Laminate</b>				
Thickness	ISO 534	µm	147 ± 5	

#### **Application and use**

This product is designed for food labelling at low temperature and deep freeze conditions.

#### **Conversion and Printing**

Suitable for water based flexo printing. We recommend to check suitability for other printing methods. This product is designed for use in thermal printing system at printing speeds up to 10 inch /250 mm per sec (based on printer's set up).

#### **Packaging**

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

#### **Shelf Life and Storage Conditions**

One year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

#### **Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi**

Mermereçiler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr  
 8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr  
 34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944