

**654731215**
**ULTRA CLEAR PP 50 TC2 -CL700- PET CLR 30\_D 654731215**

<b>Face</b>	A bi-axially oriented, gloss clear, topcoated polypropylene film.
<b>Adhesive</b>	Acrylic based, special purpose permanent ultra clear adhesive for laminates with a filmic face and backing which require UV and water whitening resistance with excellent clarity.
<b>Liner</b>	A clear polyester liner giving optimum smoothness to the adhesive layer. High strength and uniform quality permit very high speed conversion and dispensing.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>	
Basis Weight	ISO 536	g/m <sup>2</sup>	45 ± 2	
Thickness	ISO 534	µm	50 ± 3	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min. 300	(min. 7,5 N/25mm)
Loop Tack	FTM 9 glass	N/m	min. 600	(min. 15 N/25mm)
Min. appl temperature		°C	+10	
Service temperature		°C	-20 / +100	
<b>Liner</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	42 ± 1,4	
Thickness	ISO 534	µm	30 ± 1	
<b>Laminate</b>				
Thickness	ISO 534	µm	90 ± 5	

#### Application and use

For use in labelling of vodka, beer, water bottles and quality products such as luxury items, cosmetics, toiletries and household chemicals requiring durability, resistance to chemicals or moisture with "no-label- look appearance.

#### Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

#### Conversion and Printing

Topcoated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing.

#### Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

#### Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermenciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr  
 8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr  
 34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944