

676301006**GLOSSY WHITE M80 / PERMANENT / WK137P_D****Face material**

White , glossy , soft monomeric PVC .

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	107 ± 10 %
Thickness	ISO 534	µm	80 ± 10 %

**Dimensional
resistance**

Method	Unit	Target
FTM 14	mm	max. 0,4
• Adhered to steel in length .		

Adhesive

Acrylic based, permanent adhesive .

	Method	Unit	Target
Peel Adhesion 90°, 24h	FTM 2 st.st	N/m	min. 12 N/25mm
Loop Tack	FTM 9 glass	N/m	min. 15 N/25mm
Min. Appl. Temp.		°C	+ 10
Service Temperature		°C	- 40 / +80

Liner

One side siliconised white kraft paper .

	Method	Unit	Target
Basis Weight	ISO 536	g/m ²	137 ± 5 %
Thickness	ISO 534	µm	140 ± 5 %

Application and use

Suitable for short to medium term outdoor applications. It is used on advertising and promotional graphics (posters, billboards and signs).

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

Printing Methods

Suitable for solvent, eco-solvent ,UV or latex inkjet printing applications.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi

Mermerciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr
8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr
34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944