

**676302006****GLOSSY WHITE M100 / PERMANENT / WK137P\_D****Face material** White , gloss , soft monomeric PVC .

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Basis Weight	ISO 536	g/m <sup>2</sup>	130 ± 10 %
Thickness	ISO 534	µm	100 ± 10 %

<b>Dimensional resistance</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>
	FTM 14	mm	max. 0,4
	• Adhered to steel in length .		

**Adhesive** Acrylic based, permanent adhesive .

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Peel Adhesion 90° ,24h	FTM 2 st.st	N/m	min. 12 N/25mm
Loop Tack	FTM 9 glass	N/m	min. 15 N/25mm
Min. Appl. Temp.		°C	+ 10
Service Temperature		°C	- 40 / +80

**Liner** One side siliconised white kraft paper .

	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Basis Weight	ISO 536	g/m <sup>2</sup>	137 ± 5 %
Thickness	ISO 534	µm	140 ± 5 %

**Application and use**

Suitable for advertising and promotional applications (Posters, billboards and signs). And also for short and medium term outdoor applications.

**Shelf Life and Storage Conditions**

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

**Printing Methods**

Suitable for ink-jet print media , solvent and eco-solvent , UV or Latex printing applications .

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.

**Frimpeks Kimya ve Etiket Sanayi Ticaret Anonim Şirketi**

Mermerciler Sanayi Sitesi T +90 212 867 1000 frimpeks.com.tr  
8. Cad. No.:15 Beylikdüzü, F +90 212 875 1277 info@frimpeks.com.tr  
34524 İstanbul/Turkey

ISO 9001:2008 Certificate No: TR09/000944